

LB Series

22" Low Bay



250 watts MH | HPS |

ORDERING INFORMATION

Catalog #	Description	Optics	Volts	Ballast	Lamp
METAL HALIDE					
LBMH250MTMO	250 watt MH	Aluminum	Quad	CWA	MH250/U
HIGH PRESSURE SODIUM					
LBMH250MTMO	250 watt HPS	Aluminum	Quad	CWA	C250S50
480V / Lamp, Hook included					

ACCESSORIES (FIELD INSTALLED)

Catalog #	Description	Std. Pkg.
	Hook	1

FACTORY INSTALLED OPTIONS

Suffix #	Description
QRS	Quartz Restrike
480	480 Volt Ballast
C	120V Cord and Plug Installed

FEATURES

- **Die Cast Housing**
Rugged two piece housing for long lasting performance. 40° Standard ambient.
- **High Power Factor Ballast**
Class H insulation. Standard Quad volt ballast. (480V Available)
- **Slide-on Mounting Box**
Allows for quick and easy installation. 3/4" conduit connection or hook.
- **High Efficiency Refractor**
Prismatic acrylic or aluminum for efficient performance with twist lock mounting.
- **FlexBand System**
Clamp latches and locks with no tools, for easy installation and maintenance.
- **Mogul Base Socket**
Porcelain, single-piece screw shell, spring-loaded center contact.
- **Factory Installed Options**
Quartz Restrike, 480 Volt, and pre-wired Cord, Hook and Plug available.

DIMENSIONS

Approx. Weight: 27 lbs.

