



WPSQ

LIGHTING SPECIFICATION SHEET

Wallpack: square

APPLICATION:


Parking areas, perimeter lighting, entrance and walkways, waterfronts, loading platforms, recreational areas.

ELECTRICAL

UL listed for wet and damp locations.

HOUSING

Die Cast housing and hinged front frame with a chromate conversion coating and a textured bronze finish. The Slimline Wall Pack comes with molded Borosilicate prismatic glass lens.



WPSQ-GS



WPSQ-WG



DIMENSIONS

	Width	Height	Depth
WPSQ	16 1/2"	17 3/8"	7"

REFLECTOR

The reflector has porcelain mogul base socket and bracket with side access to the conduit.

BALLAST

Major brand MH, PS and HPS ballast and lamps included

ADDITIONAL FEATURES

- Includes mounting plate with integral electrical box

ORDERING INFORMATION

Catalog Number	Wattage	Voltage/Ballast	
METAL HALIDE			
WPSQ M175QL	175	Multi-Tap	
WPSQ M250QL	250	Multi-Tap	
WPSQ M400QL	400	Multi-Tap	
HIGH PRESSURE SODIUM			
WPSQ S250QL	250	Multi-Tap	
WPSQ S400QL	400	Multi-Tap	
PULSE START METAL HALIDE			
WPSQ P200QL	200	Multi-Tap	31
WPSQ P250QL	250	Multi-Tap	31
WPSQ P320QL	320	Multi-Tap	31
WPSQ P350QL	350	Multi-Tap	32
WPSQ P400QL	400	Multi-Tap	32

480V and special order 220V-50Hz for export available. Lamp included.

