



BOLFL

Louvered Flat Top Bollard

Housing:

Extruded Aluminum Housing with flush mounting base and vandal-resistant screw, flat top, powdercoat finish over a chromate conversion coating, internal ballast tray for easy maintenance.

Reflector:

Cast aluminum louvers

Lens:

Clear polycarbonate lens.

Socket:

HID: Porcelain 4KV pulse rated medium base socket with nickel-plated screw shell.

PL: Plug-in type, GX24Q-4

Mounting:

Mounting kit with anchor bolts included.

Wattage:

High Pressure Sodium: 70 to 100 watt

Metal Halide: 70 to 100 watt

Compact Fluorescent: 1 x 42 to 57 watt

Listings and Ratings:

CSA: Listed for wet locations

Ordering Information



Complete with Anchor Bolts

Model	Lamp Type	Wattage	Voltage	Finish	Lamp
BOLFL	M = Metal Halide	Metal Halide	Q (120/277)	W =White	L =Lamp Included
	S =High Pressure Sodium	50		B =Black	
		70		Z =Bronze	
	F =Fluorescent	100			
		High Pressure Sodium			
		50			
		70			
		100			
		Compact Fluorescent			
		42			
		57			



Edsun Lighting proudly assembled in the USA.