WARRANTY







KT-LED80HID-EX39-850-D

HID REPLACEMENT LED LAMP

DESCRIPTION

80W HID Replacement LED Lamp | 5000K | >83 CRI | IP64 Rated

LAMP TYPE: HID Replacement LED

BASE TYPE: EX39 (Mogul)

WATTAGE: 80W

COLOR TEMPERATURE: 5000K

METAL HALIDE EQUIVALENT: 320W

COLOR RENDERING INDEX (CRI): >83

WARRANTY: 5 Years



CUL)US LISTED

RoHS 2 Compliant

PRODUCT FEATURES

- · Replacement for Conventional Metal Halide Lamp
- DLC QPL Listed
- · Non-Dimmable; Do Not Dim
- 50,000+ Hour Lifetime
- · Environmentally Friendly: No Mercury Used
- Instant Startup
- UL Listed
- Operating Temperature: -29°C/-20°F to 60°C/140°F

EDSUN: LEDCORN80MOGUNV-50K

- Integral Driver, Eliminates the Need for External Driver or Ballast; Includes 6kV Surge Protection
- IP64 Rated; Integrated Heat Sink Quickly Dissipates Heat and Guides Water Intrusion Out of the Lamp
- Active Cooling Technology: When Internal Thermal Sensor Reaches 84°C, Lamp Power Reduces To 80% Of Max; When Sensor Cools To 65°C Lamp Powers Back Up To 100% Rated Power
- . Lamp Includes Safety Tether for Additional Security When Installing Lamp in Luminaire

OPERATING SPECIFICATIONS

ELECTRICAL CHARACTERISTICS

| Input Voltage | Power Consumption | Power Factor | Input Current |
|---------------|-------------------|--------------|------------------------------|
| 120-277Vac | 80W | >0.9 | 0.73A @ 120V 0.32A @ 277V |


RATED LIFE

| L70 (Hours) | 50,000 |
|--------------|--------|
| L/O (riours) | 50,000 |


PHOTOMETRIC CHARACTERISTICS

| Color Temperature (CCT) | 5000K |
|-----------------------------|-----------|
| Luminous Flux | 11,300 lm |
| Color Rendering Index (CRI) | >83 |
| Efficacy | 141 lm/W |
| Visible Light Area | 360° |

SPECTRAL DISTRIBUTION



LUX DISTANCE CURVE



Note: The curves indicate the illuminated area and the average illumination when the luminaire is at a different distance.

Edsun Lighting 569 W. 17 St., Hialeah, FL33010 • Ph.:305 888-8849 • email: www.edsunlighting.com • email: sales@edsunlighting.con








KT-LED80HID-EX39-850-D

HID REPLACEMENT LED LAMP





EX39-based lamps will work in both E39 and EX39 sockets.

WIRING DIAGRAM


STEP 1


Disconnect power. Disconnect and remove existing ballast, capacitor, and/or ignitor (where applicable) from fixture.


STEP 2


Rewire for line voltage to the lamp socket.

Install new LED replament lamp. Ensure lamp is operating properly when power is turned on.











PHYSICAL CHARACTERISTICS





LAMP DIMENSIONS

| A (Illuminated Length) | 4.61" | |
|------------------------|-------|--|
| B (Body Length) | 11.4" | |
| C (Diameter) | 5.12" | |

BASE TYPE: EX39 (Mogul)

ORDERING INFORMATION

| ORDER CODE | PACKAGING STYLE | PACK QTY. | ITEM STATUS |
|---------------------------|---------------------------------------|-----------|-------------|
| KT-LED80HID-EX39-850-D-DP | Distributor Pack (Individual Cartons) | 6 | Quick Ship |

CATALOG NUMBER BREAKDOWN

