



120-277V LED Compatible On-Off Photocells

RPPCB-UNV

Button Style Photocell



Features:

- Raintight For Outdoor Use
- 7" (180mm) Leads, AWG# 18
- Photoelectric Switch with 3-10 Second Delay
- UV-Stabilized Polycarbonate Enclosure & Eye
- 1/2" Thread Nipple with O-Ring Gasket

Electrical Specifications:

- Input Voltage: 120-277VAC, 50/60Hz
- On-Off Levels: 10~20Lx On(Dusk)
30~60Lx Off(Dawn)
- Ambient Temperature: -40°C ~ +70°C
- Relative Humidity: 99%
- Power Consumption: 0.4w Max.
- Tungsten: 500w
- Ballast: 850VA, 5A E-Ballast
- Listing: cULus

RPPCTL-UNV

Twistlock 3 wire Style Photocell



Features:

- IP54 Protection
- On Time Delay 0-10 Seconds;
Off Time Delay 5-20 Seconds
- UV Stabilized Polypropylene Cover & Clear Window
- IR Filtered Phototransistor
- 235J/5000A MOV
- RoHS Compliant

Electrical Specifications:

- Input Voltage: 105-305VAC
- On-Off Levels: 16Lx On(Dusk); 24Lx Off(Dawn)
- Ambient Temperature: -40°C ~ +70°C
- Relative Humidity: 99%
- Power Consumption: 0.5w
- Electrical Life: 5000 Cycles
- Tungsten: 1000w
- Ballast: 1800VA
- Fail Mode: On
- Listing: cUL-US

RPPCS-UNV

Swivel Pencil Style Photocell



Features:

- Convenient Directional Control
- Raintight For Outdoor Use
- 6" (152mm) Leads, AWG#16, AWM3321, 150°C
- Thermal Switch
- UV-Stabilized Polycarbonate Enclosure & Eye
- 1/2" CdS Photocell
- 1/2" Thread Nipple with Rubber Gasket & Zinc Alloy Lock-Nut
- Swivels 0-200°

Electrical Specifications:

- Input Voltage: 110-130VAC (P18110)
208-277VAC (P18112)
- On-Off Levels: 10~20Lx On(Dusk)
30~60Lx Off(Dawn)
- Ambient Temperature: -40°F ~ +158°F
- Relative Humidity: 96%
- Power Consumption: 1.5VA Max.
- Electrical Life: 6500 Cycles
- Tungsten: 1800w
- Ballast: 1100VA
- Listing: C-ETL-US Listed