# ED Emergency Unit

Project:	
Туре:	
Catalog #:	





STANDARD

**OPTIONAL** 









#### **ILLUMINATION**

- Long lasting, efficient ultra-bright white LED lamp heads.
- 1 wall (8 LEDs x 0.125 wall) perhead.
- High-performance chrome-plated metalized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provide optimal center-to-center spacing. High-lumen option available for increased centerto-center spacing.

#### **ELECTRICAL**

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- 3.6V long-life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

# MDUNT NG

- Surface mount via quick-connect back plate: fits most standard size junction boxes and snaps into place to make internal electrical connections.
- Top and side knockout for conduit applications.
- Suitable for wall or ceiling mount.

# HOUSING

Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

# OPTIONS


SDT: Self-diagnostic test feature performs monthly, biannually, and annually tests to ensure reliable operation and to meet electrical and life safety codes.

- HL: 12-LED heads (12 LEDs x 0.125 watt) per head provide increased center-to-center spacing
- SPV: 208/220/240 multi-tap voltage in 50/60Hz.

### WARRANTY/LISTING

- Five year warranty on all electronics and housing. Batteries pro-rated for five years.
- UL listed for damp locations. (0°C 50°C)
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA. Local and State Codes.

#### **DIMENSIONS**



Sample Part Number: RPEMGCY-LED

#### ORDERING INFORMATION

Notes:	Model	Housing Color	Options
1. Not available with SDT options.	RPEMGC-LED		SDT Self-Diagnostics-SPECIAL ORDER ONLY SP 208/220/240 Volt. 50/60Hz
			HL High-Lumen