

G24 and GX24 Flush Mount Horizontal Lamp Axis

APPLICATION and PERFORMANCE SPECIFICATION

Description: Lampholders for G24 and GX24 compact fluorescent lamps.

- Body: Casing - PBT GF
- Quick connect terminals: 18 AWG Solid and Stranded
- 660W/600V
- UL Temperature Rating T120

Type	Ref. #	Base	Lamp	Weight (g)	Packing Unit
71701	527790	G24d-1/GX24d-1	8, 10, 13 / 13	13.2	500
71702	527791	G24d-2/GX24d-2	18 / 18	13.2	500
71703	527792	G24d-3/GX24d-3	26 / 26	13.2	500
71711	527794	G24q-1/GX24q-1	10, 13 / 13	15.2	500
71712	527795	G24q-2/GX24q-2	18 / 18	15.2	500
71713	527796	G24q-3/GX24q-3	26 / 26, 32	15.2	500
71719	527800	G24q-3/-4*	26, 32 / 42	15.2	500
71714	527797	G24q-4	42	15.2	500
71715	527798	G24q-5	57	15.8	500
71716	527799	G24q-6	70	15.8	500

* May only be used in luminaires that are operated with electronic ballasts that have been certified according to the applicable standards and that cover the luminaire performance range of 26, 32, and 42W.

Physical Parameters

- Base mounting holes for self-tapping #8 screws
- Base oblong holes for #8 screws (M4)
- Rear mounting holes for self-tapping #8 screws and self-tapping #8 screws
- Front mounting holes for #4 screws (M3)
- Please see drawings for dimensions

Safety:

- cUL-US listed - Indoor Use (E110363)
- VDE/ENEC Approved



Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60400
- Lampholders meet IP20 standard

Warranty:

Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.

