

MOGUL LAMPHOLDERS

Pulse Rated • E39 Base

HID • INCANDESCENT



5 KV Pulse Rated

Porcelain body gray glazed with ceramic arc shield. Copper alloy nickel-plated screw shell with lamp grips. Copper alloy nickel-plated center contact. Lugged leads are No. 14 AWG 200°C 600V glass braid SEW-2, 16" long, stripped 1/2". Choice of bushing or screw mounting.

Standard pack: bulk

Cat. No.

- 1500W-600V • 5 KV Pulse Rated • UL Listed E-13402 • CSA Certified LR-1863
- NOM Certified 057

Cat. No.	Description
SOMOG	Mogul lampholder less wireways. (2) #8-32 screws.



4 KV Pulse Rated

Porcelain body white glazed. Copper alloy nickel-plated screw shell with lamp grips. Copper alloy nickel-plated center contact. Lugged leads are No. 14 AWG 200°C 600V glass braid SEW-2, 12" long, stripped 1/2". Choice of lock nut or screw mounting.

Standard pack: bulk

Cat. No.

- 600V • 4 KV Pulse Rated • UL Listed E-13402 • CSA Certified LR-1863
- NOM Certified 057

Cat. No.	Description
	Mogul lampholder. (2) #8-32 lock nuts.
	Mogul lampholder. (2) #8-32 screws.



*Die-cast caps and insulators available unassembled only.

SOMED: Medium base porcelain socket

SOMOG: Mogul base porcelain socket

