



# FLUORESCENT FIXTURES ENCLOSED AND GASKETED COMPONENT LIST

**VT1-2-3Lamp T5-T8-T12  
4' and 8' also tandem**

**IP-65 • IP-67**



## Accessories



## Fixture Features

- Housing - High impact glass reinforced polyester, U.L. recognized fire retardant material in one piece construction. Internal brass mounting studs to accept strip lighting fixtures..
- Diffuser - Acrylic, DR, or PC diffusers. Crepe or high performance prismatic style.
- Gasket - Poured-in-place closed cell gasket—high quality to ensure watertight fit.
- Latches - Non Metallic cam action, Celcone or stainless steel. Both with tamper-proof options.
- Mounting - Vertical, Horizontal, or overhead. For indoor and outdoor applications.
- Access - End holes (for 1/2" conduit) provided, suitable non metallic plugs (EPG) or die cast fittings.
- Regulatory - UL & CUL listed, NSF approved. IP-65 & IP-67 classification.



Part Number	Description
<b>PLVT240CASE</b>	IP67 4' Complete Unit 8 latches
<b>PLVT296CASE</b>	IP67 8' Complete Unit 12 latches
<b>PLVT220CASE</b>	IP67 2' Complete Unit 4 latches
<b>PLVT240N</b>	4' Crepe Acrylic Diffuser 6-3/8"wx49"L
<b>PLVT240</b>	4' Crepe Acrylic Diffuser 7.25"wx49"L
<b>PLVT240L</b>	4' Crepe Acrylic Diffuser 7.25"W x 52"L
<b>PLVT296L</b>	8' Crepe Acrylic Diffuser 7.25"wx102"L
<b>VT296</b>	8' Crepe Acrylic Diffuser 7.25" x 97"L
<b>RPVTMB</b>	Mounting Brackets (2 per set)
<b>PLVTLATCH</b>	Celcone Latches
<b>RPVWTWET</b>	Bushing with Locknut & O Ring, WET HUB
<b>RPVTLATCHSS</b>	Stainless Steel Latch

**ENCLOSED &  
GASKETED**