

Bollard Series

Dome Bollard with IES Type 3 Glass



BOG3

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Refractor:

IES Type 3 Clear Prismatic Borosilicate Glass Refractor

Lens:

Clear Polycarbonate Lens

Socket:

HID: Porcelain 4KV Pulse Rated Mogul Base Socket with Nickel Plated Screw Shell

PL: Plug-In Type, GX24Q-4

Mounting:

Mounting Kit with 4" (Anchor Bolts Included)

Wattage:

High Pressure Sodium: 70 to 100w

Metal Halide: 70 to 100w

Compact Fluorescent: 1 x 42 to 57w

Listings & Ratings:

CSA: Listed for Wet Locations



Kit(s)

Catalog #	Description
-----------	-------------

BOG33*	Dome Bollard HID Kit with IES Type 3 Glass
--------	--

BOG33F*	Dome Bollard PL Kit with IES Type 3 Glass
---------	---

Complete Units (Lamps Included)


Catalog #	Wattage	Voltage	Lamp	Ballast
BOG33H70R120L*	70	120	HPS	R-NPF
BOG33H100R120L*	100	120	HPS	R-NPF
BOG33H70QL*	70	Quad	HPS	HX-HPF
BOG33H100QL*	100	Quad	HPS	HX-HPF
BOG33M70QL*	70	Quad	MH	HX-HPF
BOG33M100QL*	100	Quad	MH	HX-HPF
BOG33F42EL*	1 x 42	120-277	PL	Electronic
BOG33F57EL*	1 x 57	120-277	PL	Electronic

* Specify Color: BZ=Bronze, WH=White, BK=Black

Other Wattages & Custom Colors Available Upon Request.

Bollards can be cut to custom lengths upon request.

Dimensions



BOG3

Edsun Lighting Fixture Manufg.
569 W. 17 ST., HIALEAH, FL 33010
PH.: 305-888-8849 • FAX: 305-883-0005
Email: sales@edsunlighting.com
WEB: www.edsunlighting.com

Specifications subject to change without notice.