

Round "DECO" DRUM

Circlines C, CX6, CX6SQ, CPuff 9", 11", 12", 14", 19"

WHITE Housings exposed lamps



C22X6	1)FC8T9	

C22X6	1)FC8T9	11"
C32X6	1)FC12T9	14"
C54X6	1)FC8T9 & FC12T9	14"
C40X6	1)FC16T9	19"
C72X6	1)FC12T9 & FC16T9	19"
COOVE	DDI Q	11"

C22X6-2PL9 C32X6-2PL13 14" C32X6-2PL26 14" Housing: Die-formed heavy gauge steel with high-gloss baked white enamel finish (minimum reflectance 86%) over rust inhibiting phosphate coat. Chrome model is plated finish.


Shielding: Translucent white acrylic diffuser (X6, X6SQ, Puff).

Electrical: Fluorescent wired for 120V, 60Hz AC operation, thermally protected, Class P, sound rated A, nominal power factor ballast, unless otherwise specified. UL listed.

Mounting: Ceiling mount. 54W and 72W models require both lamps to be installed.

Critical Application: Edsun strives to offer the most current product designs and value. Consequently, all Edsun products are subject to redesign and revision. Critical applications such as size, operating temperature, or sensor operation should be confirmed with the factory.

C54



C22 WHITE WHITE ACRYLIC LENSES C32












Bare bulb or diffused light (C)

Translucent white acrylic diffuser ("X6 & Puff))

- source
- Soft, even illumination; flawless

Economical, efficient lighting

Chrome set screws (X6 & Puff) •



11" or 14"

Laboratories

Easy installation and maintenance

"EM" Round drum available with battery back-up.

