



Trunion mounting for flat surfaces



BRKT: Bracket for side pole mounting  
"SHOEBOX" style



SF: Slip fitter mounting 2-3/8"OD tenon

Use this "pdf" for cutsheet:

I will place "link" on email



ZOOM

Item Description

Part Number

-Available in 5000K  
30K and 40K Optional

LEDGFXL300UNV-50K  
LEDGFXL300UNV-50K-SF  
LEDGFXL300UNV-50K-BRKT

LEDGFXL300 series is a group of architectural LED area luminaires designed to illuminate parking areas, pathways, building facades, loading docks, and a wide variety of other large, general site lighting applications. Multiple mounting options make the LEDGFXL a versatile luminaire for flood lighting, pole-, ground- and wall-mounted area lighting, and other outdoor lighting requirements.

FEATURES

- Available in 5000K
- Long-life LEDs provide 57,000 hours of operation with at least 70% of initial lumen output ( $L_{70}$ ).
- Type III models deliver 36,888 lumens & 121 lumens per watt (LPW) at 5000k.
- Universal 120-277 AC voltage (50-60Hz) is standard. 480V is also available.
- 0-10vdc dimming capability is standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Color rendering index > 80.
- Optional full glare shields, half glare shields & wire guards are available. Special order.
- Die cast aluminum housing with durable, dark bronze powder coat finish, and a heat-resistant polycarbonate lens.
- Wireway enclosure is sealed with a water-tight, silicon rubber gasket.
- Effective projected areas (EPA's) are:
  - Front = 0.37 square feet
  - Side = 0.51 square feet
  - Face = 1.74 square feet
- Threaded receptacle (1/2" NPS) for photocell. Optional arms and slip-fitters provide additional photocell mounting options.
- Easy installation in new construction or retrofit applications.